

[54] **METHOD FOR APPLYING SEALANT BETWEEN FAYING SURFACES OF AIRCRAFT WING STRUCTURES**

[75] Inventors: **Jerald L. Dickson, Kirkland; Harvey E. Green, Jr., Pacific, both of Wash.**

[73] Assignee: **The Boeing Company, Seattle, Wash.**

[21] Appl. No.: **282,117**

[22] Filed: **Jul. 10, 1981**

Related U.S. Application Data

[62] Division of Ser. No. 189,281, Sep. 22, 1980.

[51] Int. Cl.³ **B32B 7/08**
 [52] U.S. Cl. **156/92; 29/526 R;**
 29/DIG. 1; 118/306; 118/410; 156/291;
 156/295; 156/548; 156/575; 156/578; 222/330;
 222/478; 244/132; 244/133; 401/193; 401/266

[58] Field of Search 118/305, 306, 410, 411;
 156/548, 575, 578, 91, 295, 291, 92; 222/323,
 330, 478; 244/132, 131, 133; 401/193, 261, 266;
 29/526 A, 526 R, DIG. 1; 428/137

[56] References Cited

U.S. PATENT DOCUMENTS

2,555,563	6/1951	Benton	222/330 X
2,925,193	2/1960	Gibb	156/91 X
3,099,582	7/1963	Ongstad et al.	156/578 X
3,155,544	11/1964	McConnell et al.	118/410
4,157,149	6/1979	Moen	222/330 X

Primary Examiner—Robert A. Dawson

Attorney, Agent, or Firm—Conrad O. Gardner; B. A. Donahue; Nicolaas DeVogel

[57] ABSTRACT

A faying surface sealing tool for applying sealant between wing skin and spar chord joints prior to fastener installation. The faying surface sealing tool includes a plurality of spaced apartures for dispensing the sealant in bead form between each row of fastener holes and on each edge margin subsequent to joint opening.

2 Claims, 4 Drawing Figures

